



# Attestation of Compliance

Reference No. : LCS200901099AS

Applicant : Shenzhen Onlumi Technology Limited

Address : Room 218, 2F, Building D, YouDingQiChuang Area, NO.62, Heping Road, Qinghua Community, Longhua District, Shenzhen, G.D., China

Product : Solid Lock LED Strip Connector

Trade Mark : QIJIE

Model(s) : See models list

Parameters : See models list

Tested according to : EN 60998-1:2004

The submitted products have been tested by us with the listed standards.

This Attestation of Compliance is issued according to the council Directive 2014/35/EU, Referred to as the Low Voltage Directive. It confirms that the listed product complies with all essential requirements of the LVD Directive and applies only to the sample and its technical documentation submitted to Shenzhen LCS Compliance Testing Laboratory Ltd. for testing.

After preparation of the necessary technical documentation as well as the EC conformity declaration the required CE marking can be affixed on the product. Other relevant Directives have to be observed.



Date of issue: Sep 28, 2020



Shenzhen LCS Compliance Testing Laboratory Ltd.  
Room 101, 201, Building A and Room 301, Building C, Juji Industrial Park, Yabianxueziwei, Shajing Street,  
Bao'an District, Shenzhen, Guangdong, China  
Tel: (86)0755-82591330 Fax: (86)0755-82591332  
Http://www.lcs-cert.com Email: webmaster@lcs-cert.com

扫码查询真伪  
Scan, Query authenticity

1 / 2



# Attestation of Compliance

## Models list

Model name	parameter
SL8XB-2	strip to wire terminal DC3~24V / Max 6A Copper & Nylon
SL10XB-2	
SL10XB-3	
SL10XB-4	
SL8XB-2W	strip to power with strand wire Wire: 15CM 20AWG / 0.5mm <sup>2</sup> Black-Red Insulation DC3~24V / Max 6A Copper & Nylon
SL10XB-2W	
SL10XB-3W	strip to power with strand wire Wire: 15CM 20AWG / 0.5mm <sup>2</sup> (Max Gauge) Red-White-Yellow Insulation DC3~24V / Max 6A Copper & Nylon
SL10XB-4W	strip to power with strand wire Wire: 15CM 22AWG / 0.3mm <sup>2</sup> (Max Gauge) Black-Green-Red-Blue Insulation DC3~24V / Max 4A Copper & Nylon
SL8BB-2	strip to strip joint DC3~24V / Max 6A Copper & Nylon
SL10BB-2	
SL10BB-3	
SL10BB-4	
SL8BXB-2W	strip to strip bridge with strand wire 15CM 20AWG / 0.5mm <sup>2</sup> Black&Red Insulation DC3~24V / Max 6A
SL10BXB-2W	
SL10BXB-3W	strip to strip bridge with strand wire 15CM 20AWG / 0.5mm <sup>2</sup> (Max Gauge) Red-white-yellow Insulation DC3~24V / Max 6A
SL10BXB-4W	strip to strip bridge with strand wire Wire: 15CM 22AWG / 0.3mm <sup>2</sup> (Max Gauge) Black-Green-Red-Blue Insulation DC3~24V / Max 4A Copper & Nylon

