

# Electrical Wire

**Real Copper, Real Certificate  
Number, Real Quality Guarantee**



## 6 Meters Per Piece


Material	Tin plated copper, PVC
Temperature	80°C
Flame Retardant Rating	VW-1
Optional Packing	Bag / Reel / Box / Tie



Bag Packing



Reel Packing



Tie Packing

NO.	Item No	Wire Type	Wire Gauge	Pin	Insulation Color	Picture
1	18A2P-BR-6M	2468	18AWG / 0.78 mm <sup>2</sup>	2 Pin	Black- Red	
2	20A2P-BR-6M	2468	20AWG / 0.52 mm <sup>2</sup>			
3	22A2P-BR-6M	2468	22AWG / 0.34 mm <sup>2</sup>			
4	18A2P-WW-6M	2468	18AWG / 0.78 mm <sup>2</sup>	2 Pin	White -White (Zebra)	
5	20A2P-WW-6M	2468	20AWG / 0.52 mm <sup>2</sup>			
6	22A2P-WW-6M	2468	22AWG / 0.34 mm <sup>2</sup>			
7	18A3P-RWY-6M	1007	18AWG / 0.78 mm <sup>2</sup>	3 Pin	Red-White-Yellow	
8	20A3P-RWY-6M	1007	20AWG / 0.52 mm <sup>2</sup>			
9	22A3P-RWY-6M	1007	22AWG / 0.34 mm <sup>2</sup>			
10	18A3P-RGW-6M	1007	18AWG / 0.78 mm <sup>2</sup>	3 Pin	Red-Green-White	
11	20A3P-RGW-6M	1007	20AWG / 0.52 mm <sup>2</sup>			
12	22A3P-RGW-6M	1007	22AWG / 0.34 mm <sup>2</sup>			
13	18A4P-BKGRB-6M	1007	18AWG / 0.78 mm <sup>2</sup>	4 Pin	Black-Green-Red-Blue	
14	20A4P-BKGRB-6M	1007	20AWG / 0.52 mm <sup>2</sup>			
15	22A4P-BKGRB-6M	1007	22AWG / 0.34 mm <sup>2</sup>			
16	18A4P-WX4-6M	1007	18AWG / 0.78 mm <sup>2</sup>	4 Pin	All White (zebra)	
17	20A4P-WX4-6M	1007	20AWG / 0.52 mm			
18	22A4P-WX4-6M	1007	22AWG / 0.34 mm <sup>2</sup>			
19	18A5P-BKGRBW-6M	1007	18AWG / 0.78 mm <sup>2</sup>	5 Pin	Black-Green-Red-Blue-White	
20	20A5P-BKGRBW-6M	1007	20AWG / 0.52 mm <sup>2</sup>			
21	22A5P-BKGRBW-6M	1007	22AWG / 0.34 mm <sup>2</sup>			
22	18A6P-BKGRBWY-6M	1007	18AWG / 0.78 mm <sup>2</sup>	6 Pin	Black-Green-Red-Blue-White-Yellow	
23	20A6P-BKGRBWY-6M	1007	20AWG / 0.52 mm <sup>2</sup>			
24	22A6P-BKGRBWY-6M	1007	22AWG / 0.34 mm <sup>2</sup>			

## 25 Meters Per Piece

Material	Tin plated copper
Temperature	80°C
Flame Retardant Rating	VW-1
Optional Packing	Bag / Reel / Box / Tie



Bag Packing



Reel Packing



Box Packing



Tie Packing

NO.	Item No	Wire Type	Wire Gauge	Pin	Insulation Color	Picture
1	18A2P-BR-25M	2468	18AWG / 0.78 mm <sup>2</sup>	2 Pin	Black- Red	
2	20A2P-BR-25M	2468	20AWG / 0.52 mm <sup>2</sup>			
3	22A2P-BR-25M	2468	22AWG / 0.34 mm <sup>2</sup>			
4	18A2P-WW-25M	2468	18AWG / 0.78 mm <sup>2</sup>	2 Pin	White -White (Zebra)	
5	20A2P-WW-25M	2468	20AWG / 0.52 mm <sup>2</sup>			
6	22A2P-WW-25M	2468	22AWG / 0.34 mm <sup>2</sup>			
7	18A3P-RWY-25M	1007	18AWG / 0.78 mm <sup>2</sup>	3 Pin	Red-White-Yellow	
8	20A3P-RWY-25M	1007	20AWG / 0.52 mm <sup>2</sup>			
9	22A3P-RWY-25M	1007	22AWG / 0.34 mm <sup>2</sup>			
10	18A3P-RGW-25M	1007	18AWG / 0.78 mm <sup>2</sup>	3 Pin	Red-Green-White	
11	20A3P-RGW-25M	1007	20AWG / 0.52 mm <sup>2</sup>			
12	22A3P-RGW-25M	1007	22AWG / 0.34 mm <sup>2</sup>			
13	18A4P-BKGRB-25M	1007	18AWG / 0.78 mm <sup>2</sup>	4 Pin	Black-Green-Red-Blue	
14	20A4P-BKGRB-25M	1007	20AWG / 0.52 mm <sup>2</sup>			
15	22A4P-BKGRB-25M	1007	22AWG / 0.34 mm <sup>2</sup>			
16	18A4P-WX4-25M	1007	18AWG / 0.78 mm <sup>2</sup>	4 Pin	All White (zebra)	
17	20A4P-WX4-25M	1007	20AWG / 0.52 mm			
18	22A4P-WX4-25M	1007	22AWG / 0.34 mm <sup>2</sup>			
19	18A5P-BKGRBW-25M	1007	18AWG / 0.78 mm <sup>2</sup>	5 Pin	Black-Green-Red-Blue-White	
20	20A5P-BKGRBW-25M	1007	20AWG / 0.52 mm <sup>2</sup>			
21	22A5P-BKGRBW-25M	1007	22AWG / 0.34 mm <sup>2</sup>			
22	18A6P-BKGRBWY-25M	1007	18AWG / 0.78 mm <sup>2</sup>	6 Pin	Black-Green-Red-Blue-White-Yellow	
23	20A6P-BKGRBWY-25M	1007	20AWG / 0.52 mm <sup>2</sup>			
24	22A6P-BKGRBWY-25M	1007	22AWG / 0.34 mm <sup>2</sup>			



## 50 Meters Per Piece

Material	Tin plated copper
Temperature	80°C
Flame Retardant Rating	VW-1
Optional Packing	Bag / Reel / Box / Tie



Bag Packing



Box Packing



Tie Packing

NO.	Item No	Wire Type	Wire Gauge	Pin	Insulation Color	Picture
1	18A2P-BR-50M	2468	18AWG / 0.78 mm <sup>2</sup>	2 Pin	Black- Red	
2	20A2P-BR-50M	2468	20AWG / 0.52 mm <sup>2</sup>			
3	22A2P-BR-50M	2468	22AWG / 0.34 mm <sup>2</sup>			
4	18A2P-WW-50M	2468	18AWG / 0.78 mm <sup>2</sup>	2 Pin	White -White (Zebra)	
5	20A2P-WW-50M	2468	20AWG / 0.52 mm <sup>2</sup>			
6	22A2P-WW-50M	2468	22AWG / 0.34 mm <sup>2</sup>			
7	18A3P-RWY-50M	1007	18AWG / 0.78 mm <sup>2</sup>	3 Pin	Red-White-Yellow	
8	20A3P-RWY-50M	1007	20AWG / 0.52 mm <sup>2</sup>			
9	22A3P-RWY-50M	1007	22AWG / 0.34 mm <sup>2</sup>			
10	18A3P-RGW-50M	1007	18AWG / 0.78 mm <sup>2</sup>	3 Pin	Red-Green-White	
11	20A3P-RGW-50M	1007	20AWG / 0.52 mm <sup>2</sup>			
12	22A3P-RGW-50M	1007	22AWG / 0.34 mm <sup>2</sup>			
13	18A4P-BKGRB-50M	1007	18AWG / 0.78 mm <sup>2</sup>	4 Pin	Black-Green-Red-Blue	
14	20A4P-BKGRB-50M	1007	20AWG / 0.52 mm <sup>2</sup>			
15	22A4P-BKGRB-50M	1007	22AWG / 0.34 mm <sup>2</sup>			
16	18A4P-WX4-50M	1007	18AWG / 0.78 mm <sup>2</sup>	4 Pin	All White (zebra)	
17	20A4P-WX4-50M	1007	20AWG / 0.52 mm			
18	22A4P-WX4-50M	1007	22AWG / 0.34 mm <sup>2</sup>			
19	18A5P-BKGRBW-50M	1007	18AWG / 0.78 mm <sup>2</sup>	5 Pin	Black-Green-Red-Blue-White	
20	20A5P-BKGRBW-50M	1007	20AWG / 0.52 mm <sup>2</sup>			
21	22A5P-BKGRBW-50M	1007	22AWG / 0.34 mm <sup>2</sup>			
22	18A6P-BKGRBWY-50M	1007	18AWG / 0.78 mm <sup>2</sup>	6 Pin	Black-Green-Red-Blue-White-Yellow	
23	20A6P-BKGRBWY-50M	1007	20AWG / 0.52 mm <sup>2</sup>			
24	22A6P-BKGRBWY-50M	1007	22AWG / 0.34 mm <sup>2</sup>			

## 305 Meters Per Piece

Material	Tin plated copper
Temperature	80°C
Flame Retardant Rating	VW-1
Optional Packing	Roll with Film / Plastic Spool



Roll with Film Packing



Plastic Spool Packing

NO.	Item No	Wire Type	Wire Gauge	Pin	Insulation Color	Picture
1	18A2P-BR-305M	2468	18AWG / 0.78 mm <sup>2</sup>	2 Pin	Black- Red	
2	20A2P-BR-305M	2468	20AWG / 0.52 mm <sup>2</sup>			
3	22A2P-BR-305M	2468	22AWG / 0.34 mm <sup>2</sup>			
4	18A2P-WW-305M	2468	18AWG / 0.78 mm <sup>2</sup>	2 Pin	White -White (Zebra)	
5	20A2P-WW-305M	2468	20AWG / 0.52 mm <sup>2</sup>			
6	22A2P-WW-305M	2468	22AWG / 0.34 mm <sup>2</sup>			
7	18A3P-RWY-305M	1007	18AWG / 0.78 mm <sup>2</sup>	3 Pin	Red-White-Yellow	
8	20A3P-RWY-305M	1007	20AWG / 0.52 mm <sup>2</sup>			
9	22A3P-RWY-305M	1007	22AWG / 0.34 mm <sup>2</sup>			
10	18A3P-RGW-305M	1007	18AWG / 0.78 mm <sup>2</sup>	3 Pin	Red-Green-White	
11	20A3P-RGW-305M	1007	20AWG / 0.52 mm <sup>2</sup>			
12	22A3P-RGW-305M	1007	22AWG / 0.34 mm <sup>2</sup>			
13	18A4P-BKGRB-305M	1007	18AWG / 0.78 mm <sup>2</sup>	4 Pin	Black-Green-Red-Blue	
14	20A4P-BKGRB-305M	1007	20AWG / 0.52 mm <sup>2</sup>			
15	22A4P-BKGRB-305M	1007	22AWG / 0.34 mm <sup>2</sup>			
16	18A4P-WX4-305M	1007	18AWG / 0.78 mm <sup>2</sup>	4 Pin	All White (zebra)	
17	20A4P-WX4-305M	1007	20AWG / 0.52 mm			
18	22A4P-WX4-305M	1007	22AWG / 0.34 mm <sup>2</sup>			
19	18A5P-BKGRBW-305M	1007	18AWG / 0.78 mm <sup>2</sup>	5 Pin	Black-Green-Red-Blue-White	
20	20A5P-BKGRBW-305M	1007	20AWG / 0.52 mm <sup>2</sup>			
21	22A5P-BKGRBW-305M	1007	22AWG / 0.34 mm <sup>2</sup>			
22	18A6P-BKGRBWY-305M	1007	18AWG / 0.78 mm <sup>2</sup>	6 Pin	Black-Green-Red-Blue-White-Yellow	
23	20A6P-BKGRBWY-305M	1007	20AWG / 0.52 mm <sup>2</sup>			
24	22A6P-BKGRBWY-305M	1007	22AWG / 0.34 mm <sup>2</sup>			